









"ARE YOU READY FOR THE FUTURE WHEN IT COMES TO THE HYGIENIC HANDLING OF YOUR FOOD PRODUCTS?"

Jonge Poerink Conveyors has developed a revolutionary alternative for the wire mesh curve. A very robust belt that, if necessary, is easy to repair - in contrast to existing wire mesh belts. The completely new conveyor belt has been designed in accordance with USDA and FDA guidelines, thus ensuring the highest of hygienic standards.

The new designed belt belt further offers the same benefits as the wire mesh belt. An open structure, which makes it possible to thoroughly clean the belt, both dry and wet washdown execution. Small surface of contact with the product and resistant to both high and low temperatures (-30 to +80°C).

In addition, the centrally positioned drive offers optimum flexibility. This makes it possible to run the belt in both directions.

FEATURES


- Open belt
- Robust
- Design in accordance with USDA/FDA
- Central drive
- Easy to clean
- Wash down
- Most hygienic modular belt available in the industry

INDUSTRIES (EXAMPLES)

- Snacks
- Bakery
- Fish
- Meat



TECHNICAL SPECIFICATIONS



Belt material	POM/Acetal Food-approved
Rod material	Stainless steel
Supports material	UHMW
Belt radius on in- and outfeed	21 mm
Belt speed	max. 30 m/min
Product temperature range	-30°C to +80°C
Ambient temperature range	-30°C to +40°C



BELT WIDTH (MM/INCH) VERSUS INSIDE RADIUS (MM)

Belt width (mm/inch)	Inside radius (mm)
203 / 8"	406, 610, 813, 1016, 1219
406 / 16"	406, 610, 813, 1016
610 / 24"	406, 610, 813
813 / 32"	406, 610
1016 / 40"	406





CONVEYORS TO IMPROVE YOUR EFFICIENCY Jonge Poerink Conveyors designs and builds conveyors to optimise your product flow. Based on more than 90 years of experience in innovating efficiency, our conveyors help to optimise the throughput of your production line and improve your yield.